

## RF DATA

ITEM		SPECIFICATIONS	REMARKS
Frequency Range		2304-2485M	Bandwidth Range $\pm$ 10MHz
Working Voltage		28V	24-30V
INput Power (Max)		$\leq$ 10dBm	
Output Power (Max)		$\geq$ 47 dBm	50W
Gain (Max)		47 $\pm$ 1dB	
Ripple in Band		$\leq$ 3 dB	Peak
Enable Control		Customize	3-28V
EN switch frequency		10000 times	Switching time interval $\geq$ 3S
Output VSWR		$\leq$ 2	
High Low Temperatu re Test	Working Temperature	-20 $\sim$ +65 $^{\circ}$ C	Working properly
	Gain Stability	$\pm$ 1 dB	At -20 $^{\circ}$ C $\sim$ +55 $^{\circ}$ C
	Power Stability	$\pm$ 1 dB	At -20 $^{\circ}$ C $\sim$ +55 $^{\circ}$ C
Working Current		$\leq$ 4.5A @+28V dc;	CW output 50W
Power Supply Port		Positive and negative lines	24-28V; GND
RF Output Connector		SMA-Female	
Green LED Indicator Light		CD Power ON/OFF	It lights up when the power supply voltage is present and turns off when the power is switched off.
Blue LED Indicator Light		RF Power ON/OFF	It turns off when the output power is below 5–10 dBm, and turns on when the output power is within the normal range.
Red LED Indicator Light		Temperature alarm indicator light	When the temperature exceeds 100 $^{\circ}$ C, it lights up but does not turn off the PA.



